TECHNICAL PAPER **February 2026**

Reducing Wiring Complexity and Improving Reliability in Double Solenoid Valve Applications

Executive Summary

Hydraulic and electro-pneumatic control systems increasingly rely on electrically actuated solenoid valves to achieve precise, repeatable control of fluid power. As system complexity grows, so does the number of electrical connections required to support valve operation. In double solenoid valve configurations, traditional wiring methods typically use separate connectors and cable assemblies for each solenoid. While effective, this approach introduces additional connection points, increases installation complexity, and raises the potential for electrical and environmental failure.

Each additional connector interface represents a potential point of vulnerability. Exposure to vibration, moisture, contaminants, and mechanical stress can degrade connection integrity over time, leading to intermittent operation, troubleshooting challenges, and unplanned downtime. Additionally, increased wiring complexity contributes to longer installation times, higher labor costs, and greater variability during equipment assembly.

Integrated connector systems offer a practical engineering solution to these challenges by consolidating multiple electrical interfaces into a single sealed assembly. By reducing the number of independent connection points and simplifying cable routing, integrated connectors improve overall system reliability while reducing installation and maintenance effort.

The Canfield Connector 5JMC integrated dual-DIN connector assembly is designed specifically to address the limitations of traditional dual-solenoid wiring architectures. By combining two solenoid connections into a single rugged, over molded assembly, the 5JMC simplifies electrical integration, enhances environmental protection, and improves long-term operational reliability

in demanding hydraulic and industrial applications.

Introduction: The Evolution of Hydraulic and Electro-Pneumatic Systems

Hydraulic and electro-pneumatic systems play a critical role in modern industrial, mobile, and automation equipment. From agricultural machinery and off-highway vehicles to industrial automation and material handling systems, electrically actuated solenoid valves enable precise control of fluid power to support increasingly sophisticated machine functions.

As equipment capabilities have advanced, so has the density and complexity of valve manifolds and control systems. Engineers are tasked with integrating more functionality into smaller physical spaces while maintaining reliability, serviceability, and manufacturing efficiency. Double solenoid valve configurations are commonly used to provide directional control, redundancy, or multi-state functionality, but these configurations also increase the number of electrical connections required within the system.

Traditional approaches to wiring double solenoid valves rely on separate connectors and individual cable assemblies for each solenoid coil. While this architecture has been widely adopted, it introduces additional connection interfaces, sealing surfaces, and cable routing requirements. Each of these elements adds complexity to the system and creates potential points of failure.

Electrical connectivity is frequently exposed to harsh operating environments, including vibration, moisture, temperature fluctuations, and contamination. Over time, these conditions can compromise connector integrity, leading to electrical faults, maintenance challenges, and reduced equipment reliability.

As a result, electrical connector design has become a critical factor in overall system performance. Reducing wiring complexity, improving environmental protection, and enhancing connection reliability are essential engineering objectives for modern hydraulic and electro-pneumatic systems. Integrated connector solutions represent an important advancement in addressing these challenges while supporting the continued evolution of compact, high-performance equipment.

Traditional Dual Solenoid Wiring Architecture and Its Limitations

Double solenoid valves are widely used in hydraulic and electro-pneumatic systems to provide reliable directional control and multi-state functionality. Each solenoid coil must be electrically connected to the control system in order to actuate the valve. In traditional implementations, this is accomplished using separate DIN connectors and individual cable assemblies for each solenoid.

While this approach provides independent control of each coil, it also introduces additional electrical interfaces, cable routing requirements, and environmental exposure points. Each solenoid requires its own connector, sealing interface, and cable path from the control system. As a result, a single double solenoid valve requires at least two connector assemblies and associated wiring infrastructure.

The increased number of connection points has several important implications for system performance and reliability. Each connector interface represents a potential entry point for moisture, dust, and contaminants. In hydraulic and mobile equipment applications, connectors are often exposed to vibration, mechanical shock, oil, and temperature fluctuations. These conditions can degrade connector seals, loosen mechanical interfaces, and compromise electrical continuity over time.

Cable routing complexity is another significant challenge. Multiple cable runs must be routed through confined spaces within control enclosures, along manifolds, or through protective conduit. This increases the likelihood of cable strain, abrasion, or improper routing during installation. Variability in assembly practices can lead to inconsistent installation quality, increasing the risk of premature failure.

In addition to reliability concerns, traditional wiring architectures also impact manufacturing efficiency. Installing multiple connectors and routing separate cables requires additional assembly time and labor. Each connection must be properly terminated, secured, and verified, increasing the potential for installation errors. Over the lifecycle of the equipment, maintenance personnel must also inspect and troubleshoot multiple independent connections, increasing service time and complexity.

The cumulative effect of these factors is an increase in the overall number of potential failure points within the system. Even when individual connectors meet environmental and electrical specifications, the probability of system-level failure increases as the total number of independent interfaces grows.

As hydraulic and electro-pneumatic systems continue to evolve toward higher performance, increased valve density, and more compact designs, the limitations of traditional dual connector architectures become more pronounced. Engineers must balance the need for reliable electrical connectivity with the practical constraints of space, installation efficiency, and long-term durability.

These challenges highlight the importance of reducing connection complexity and improving electrical integration through more efficient connector design approaches. Integrated connector systems offer a means to address these limitations by consolidating multiple electrical interfaces into a single, environmentally sealed assembly.

Engineering Requirements for Modern Hydraulic Connectivity

As hydraulic and electro-pneumatic systems have become more compact and functionally complex, the requirements placed on electrical connectivity have evolved accordingly. Connectors are no longer passive components but essential elements that directly influence system reliability, installation efficiency, and long-term performance. Engineers designing modern equipment must consider connectivity as a critical part of the overall system architecture.

One of the primary requirements is reducing the number of independent connection points within the system. Each connector interface introduces mechanical and environmental exposure that can compromise electrical continuity over time. Minimizing these interfaces reduces the number of potential failure points and improves overall system reliability.

Environmental protection is another essential consideration. Hydraulic systems frequently operate in conditions where connectors are exposed to moisture, oil, dust, and temperature fluctuations. Effective connector designs must maintain seal integrity throughout the equipment's service life, preventing contaminant ingress that can lead to corrosion or intermittent electrical faults. Connectors must also withstand vibration and mechanical stress without degrading performance.

Installation efficiency is equally important, particularly in high-volume manufacturing environments. Equipment manufacturers seek to reduce assembly time, simplify wiring processes, and minimize variability between installations. Connector systems that simplify cable routing and reduce installation steps help improve production consistency while lowering labor requirements.

Mechanical durability and strain relief are also critical factors. Cable assemblies must maintain secure electrical continuity even when subjected to movement, vibration, or repeated thermal cycling. Proper strain relief and integrated construction help distribute mechanical loads and prevent stress concentration at termination points.

In addition, diagnostic visibility has become increasingly valuable. Connectors that provide clear visual indication of electrical status allow technicians to quickly confirm operation and identify potential faults, reducing troubleshooting time and improving maintenance efficiency.

Ultimately, modern hydraulic connectivity solutions must deliver a combination of reliability, environmental protection, installation efficiency, and serviceability. Connector designs that address these requirements support improved system performance, reduce lifecycle maintenance demands, and enhance overall equipment reliability.

Meeting these engineering objectives requires a shift from traditional multi-component wiring approaches toward more integrated connectivity solutions that simplify system architecture while improving durability and long-term performance.

Integrated Connector Design Principles: Consolidating Electrical Interfaces

One of the most effective ways to improve electrical reliability in hydraulic and electro-pneumatic systems is to reduce the total number of independent connection interfaces. Each electrical connection introduces potential vulnerabilities, including sealing interfaces that may degrade, mechanical joints that may loosen under vibration, and termination points that may experience stress over time. By consolidating multiple electrical connections into a single integrated assembly, engineers can significantly reduce these risks while simplifying overall system architecture.

Integrated connector designs combine multiple electrical pathways within a single housing, allowing multiple solenoid coils or devices to be controlled through one consolidated cable interface. This approach reduces the number of independent connectors, cable entry points, and sealing surfaces required within the system. Fewer interfaces directly translate to fewer opportunities for environmental ingress, mechanical stress concentration, or electrical discontinuity.

In addition to improving environmental protection, integrated connector systems also simplify cable routing. Traditional wiring architectures require multiple cable runs to be routed through confined spaces, increasing the potential for cable interference, improper routing, or strain on individual connectors. Consolidated connector assemblies allow a single cable to carry multiple electrical signals, reducing routing complexity and improving overall wiring organization.

Mechanical durability is also improved through integrated construction. Over molded connector assemblies provide continuous strain relief along the cable entry point and eliminate gaps between connector components. This helps distribute mechanical forces more evenly and reduces localized stress that can lead to connector or wire fatigue. The result is a more robust electrical interface capable of withstanding the vibration and movement common in hydraulic and mobile equipment.

Integrated connectors also contribute to improved manufacturing consistency. By reducing the number of installation steps and independent connections, integrated assemblies help minimize variability during equipment assembly. This improves production efficiency and reduces the likelihood of installation errors that could affect long-term performance.

From a reliability engineering perspective, system robustness is closely tied to the number of independent components and interfaces. Reducing the number of connectors and simplifying the electrical architecture improves the overall reliability profile of the system. Integrated

connector designs represent a practical and effective method for achieving this goal while supporting the increasing performance and compactness requirements of modern hydraulic and electro-pneumatic equipment.

Technical Overview of the 5JMC Integrated Connector System

The Canfield Connector 5JMC Series integrated connector system was developed to address the limitations associated with traditional dual-connector wiring architectures used in double solenoid valve applications. By consolidating two standard DIN solenoid connections into a single integrated assembly, the 5JMC simplifies electrical integration while improving environmental protection and mechanical durability.

The 5JMC utilizes a single multi-conductor cable to provide independent electrical pathways to both solenoid coils. This allows system designers to maintain full control functionality while reducing the number of external cable runs and connection interfaces. The consolidated design improves wiring organization and reduces the physical space required for cable routing within control enclosures or along valve manifolds.

A key feature of the 5JMC is its fully molded construction. The connector housing and cable interface are over molded using durable polyurethane material, which provides continuous environmental sealing and integrated strain relief. This over molded design eliminates gaps between connector components and reduces the likelihood of moisture or contaminant ingress. Integrated gasket sealing at the DIN interface further enhances environmental protection, allowing the connector to perform reliably in harsh industrial and mobile environments.

The connector assembly is designed with a low-profile 90-degree cable exit, allowing installation in confined spaces commonly encountered in hydraulic valve manifolds and compact equipment designs. This geometry helps reduce cable bending stress and improves cable routing efficiency.

Optional integrated LED indicators provide visual confirmation of solenoid activation, allowing operators and maintenance personnel to quickly verify system status without the need for diagnostic equipment. This feature supports faster troubleshooting and reduces equipment downtime.

The 5JMC Series is compatible with standard DIN 43650 solenoid valve interfaces and supports independent or parallel operation of the connected solenoids. This ensures compatibility with a wide range of hydraulic and electro-pneumatic systems while maintaining the flexibility required for modern equipment designs.

Through its integrated construction, environmental sealing, and simplified electrical architecture, the 5JMC provides a robust and efficient connectivity solution for double solenoid valve applications.

Reliability Improvements Through Connection Consolidation

Electrical reliability in hydraulic and electro-pneumatic systems is strongly influenced by the number and quality of connection interfaces within the system. Each connector introduces a mechanical and environmental boundary that must maintain electrical continuity while resisting exposure to vibration, contaminants, and mechanical stress. As the number of independent connectors increases, so does the cumulative probability of connection-related failure.

Traditional dual solenoid wiring architectures require separate connectors and cable assemblies for each solenoid coil. Each connector introduces its own sealing interface, mechanical retention features, and termination points. Over time, these interfaces may experience degradation due to environmental exposure, thermal cycling, or mechanical vibration. Even when individual connectors meet environmental and electrical specifications, the presence of multiple independent interfaces increases the overall risk of system-level failure.

Integrated connector systems such as the 5JMC improve reliability by reducing the number of external connection points and consolidating multiple electrical pathways into a single sealed assembly. This consolidation reduces the number of environmental entry points where moisture, dust, or contaminants could compromise electrical performance. A single over molded cable entry provides continuous sealing and integrated strain relief, minimizing stress on internal conductors.

Mechanical reliability is also enhanced through improved strain distribution. In traditional wiring configurations, multiple independent cables may be subject to movement or vibration, increasing the risk of fatigue at termination points. The integrated construction of the 5JMC reduces cable movement and distributes mechanical forces more evenly along the cable assembly. This reduces localized stress and helps maintain long-term electrical integrity.

Consistency of installation also contributes to improved reliability. Integrated connector assemblies reduce the number of installation steps and minimize variability associated with manual connector termination and cable routing. This improves assembly repeatability and reduces the likelihood of installation-related faults.

By reducing the number of independent connection interfaces and improving environmental sealing, integrated connector systems help improve the overall reliability profile of hydraulic and electro-pneumatic systems. The result is more consistent electrical performance, reduced maintenance requirements, and improved long-term operational stability.

Installation, Manufacturing, and Lifecycle Efficiency Benefits

In addition to improving electrical reliability, integrated connector systems provide meaningful advantages during equipment assembly and throughout the operational lifecycle. Traditional

dual-connector wiring architectures require multiple cable assemblies to be installed, routed, secured, and verified. Each individual connector must be properly aligned, sealed, and connected, increasing assembly time and the potential for installation variability.

By consolidating two solenoid connections into a single integrated assembly, the 5JMC reduces the number of installation steps required. A single cable assembly replaces multiple independent cable runs, simplifying routing and reducing the physical complexity of the wiring layout. This allows assembly personnel to complete installation more efficiently while reducing the opportunity for wiring errors or improper connections.

Improved wiring organization also contributes to cleaner equipment design. Reduced cable congestion improves accessibility within control enclosures and around valve manifolds, making equipment easier to assemble, inspect, and service. This is particularly beneficial in compact systems where space constraints can complicate cable routing and connector access.

Manufacturing consistency is enhanced through the use of preassembled, over molded connector systems. Integrated assemblies reduce the variability associated with manual connector termination and independent cable installation. This helps improve production repeatability and reduces the likelihood of installation-related defects that could affect long-term performance.

Lifecycle maintenance efficiency is also improved. With fewer connectors and cable assemblies to inspect, maintenance personnel can more quickly evaluate electrical connectivity during routine service. Integrated LED indicators, when included, provide immediate visual confirmation of solenoid activation, further simplifying troubleshooting and fault isolation.

By reducing installation complexity, improving manufacturing consistency, and simplifying maintenance procedures, integrated connector systems help lower total lifecycle costs while supporting more efficient equipment production and long-term operation.

Environmental Performance in Mobile and Industrial Applications

Hydraulic and electro-pneumatic systems frequently operate in environments where electrical connectors are exposed to challenging conditions. Mobile equipment, agricultural machinery, and industrial automation systems often encounter vibration, mechanical shock, moisture, oil exposure, dust, and temperature fluctuations. These environmental factors can degrade connector seals, weaken electrical interfaces, and contribute to long-term reliability issues.

Connector assemblies must maintain electrical continuity and environmental sealing despite continuous exposure to these stresses. Traditional connector designs that rely on multiple independent components may be more susceptible to environmental ingress at sealing interfaces, particularly as connectors age or experience repeated mechanical loading.

The 5JMC integrated connector system addresses these challenges through its fully molded construction and integrated sealing design. The over molded polyurethane housing creates a continuous protective barrier that reduces the likelihood of moisture or contaminant ingress. Integrated strain relief helps prevent mechanical stress from concentrating at termination points, preserving conductor integrity during vibration and movement.

By reducing the number of external connection points and providing robust environmental sealing, integrated connector assemblies help maintain consistent electrical performance in demanding operating environments. This supports improved equipment reliability and reduces the likelihood of connector-related failures in mobile and industrial applications.

Diagnostic and Maintenance Advantages of Integrated LED Indicators

Efficient troubleshooting and maintenance are critical to minimizing equipment downtime and maintaining operational productivity. In traditional wiring configurations, verifying solenoid activation often requires the use of external diagnostic tools such as multimeters or system-level monitoring. This process can increase service time and make fault isolation more difficult, particularly in complex hydraulic systems with multiple valves and electrical connections.

Integrated LED indicators provide immediate visual confirmation of electrical status at the point of connection. When a solenoid coil is energized, the indicator illuminates, allowing operators and technicians to quickly verify proper operation. This reduces the time required to identify electrical faults and helps distinguish between electrical and mechanical issues.

The optional LED indicators available with the 5JMC connector system improve diagnostic visibility without requiring additional components or wiring. By enabling faster fault identification and simplifying routine inspection, integrated visual indicators help reduce maintenance time and support more efficient system serviceability.

Application Examples and Use Cases

Integrated connector systems such as the 5JMC are particularly well suited for applications where double solenoid valves are used in compact, high-performance hydraulic and electro-pneumatic systems. These systems are commonly found in mobile equipment, industrial automation, and fluid power applications where electrical reliability and installation efficiency are essential.

Hydraulic valve manifolds used in mobile and off-highway equipment, including agricultural machinery and utility vehicles, often operate in environments characterized by vibration, moisture, and temperature variation. Integrated connector assemblies help maintain reliable electrical connections while simplifying wiring architecture in these demanding conditions.

Industrial automation systems also benefit from integrated connector solutions. Manufacturing equipment frequently incorporates multiple solenoid valves within confined control enclosures. Reducing the number of cable assemblies and connection points improves wiring organization and simplifies installation while supporting consistent system performance.

Material handling systems, packaging equipment, and fluid control systems represent additional applications where compact connector design and reliable electrical performance are critical. In these environments, integrated connector assemblies help reduce wiring complexity and improve serviceability while supporting efficient equipment operation.

By addressing the electrical connectivity challenges common to these applications, integrated connector systems help improve system reliability, simplify installation, and support long-term equipment performance.

Conclusion

As hydraulic and electro-pneumatic systems continue to evolve toward greater functionality, higher component density, and more compact designs, electrical connectivity has become an increasingly important factor in overall system performance and reliability. Traditional dual connector wiring architectures, while functional, introduce additional connection points, increase installation complexity, and create more opportunities for environmental and mechanical stress to affect electrical continuity.

Each independent connector interface represents a potential point of vulnerability. Environmental exposure, vibration, and mechanical strain can degrade connector performance over time, increasing the likelihood of maintenance requirements and unplanned downtime. Reducing the number of connection interfaces is an effective method for improving system reliability and simplifying electrical integration.

Integrated connector systems provide a practical engineering solution by consolidating multiple electrical pathways into a single sealed assembly. This approach reduces wiring complexity, improves environmental protection, and enhances installation efficiency while maintaining full control functionality.

The Canfield Connector 5JMC integrated connector system applies these principles by combining dual DIN solenoid connections into a single over molded assembly. By simplifying wiring architecture and improving connection integrity, integrated connector designs such as the 5JMC help support reliable, efficient operation in modern hydraulic and electro-pneumatic systems.

About Canfield Connector

Canfield Connector, headquartered in Youngstown, Ohio, designs and manufactures high-quality electrical connectors and connectivity solutions for hydraulic, industrial automation, mobile equipment, and fluid power applications. With decades of experience in connector engineering and manufacturing, Canfield Connector specializes in rugged, application-specific solutions that improve reliability and simplify electrical integration. The company's product portfolio includes DIN valve connectors, Deutsch-style connectors, custom cable assemblies, and integrated connector systems designed to perform in demanding environments. Through continuous product innovation and in-house manufacturing capabilities, Canfield Connector supports equipment manufacturers worldwide with reliable and efficient electrical connectivity solutions.



Integrated 5JMC Connector Assembly Installed on Double Solenoid Valve



Traditional Dual DIN Connector Configuration