TECHNICAL PAPER **November 2025**

The Hidden Cost of Connector Failures — and How the GTMC from Canfield Connector Solves It

Executive Summary

In industries where every minute of downtime carries a measurable cost, small components often determine large outcomes. Electrical connectors—though rarely in the spotlight—play a decisive role in maintaining system continuity in mobile and industrial equipment. When these connectors fail, machines stop, production halts, and maintenance budgets swell. The root causes are well known: vibration-induced loosening, corrosion from fluid ingress, improper field wiring, and environmental degradation that erode seal integrity over time.

Canfield Connector developed the GatorMate GTMC Deutsch Style Duo Connector to directly address those weak links. By combining two Deutsch-style terminations within a single overmolded body, the GTMC eliminates redundant junctions and minimizes the primary paths for moisture or mechanical stress to compromise a circuit. The result is a sealed, strain-relieved, IP67-rated connection engineered for long-term performance in off-highway, agricultural, and industrial automation environments.

This paper examines the hidden economic impact of connector failures and outlines how the GTMC's integrated overmold design lowers total cost of ownership. Through detailed discussion of its construction, validation testing, and field performance, it demonstrates how a purpose-built connector can improve equipment reliability, simplify harness design, and extend service life—ultimately delivering measurable value to OEMs and end users alike.

Introduction: The Overlooked Link in System Reliability

From precision factory cells to heavy-duty mobile machinery, electrical connectors form the circulatory system of modern equipment. Every solenoid, sensor, and actuator relies on these

junctions to carry power and signal through environments that range from clean control panels to mud-covered job sites. Yet in many reliability studies, connectors rank among the top three sources of electrical failure. A single compromised seal or fatigued crimp can disable an entire hydraulic circuit or halt an automated process.

The financial implications extend well beyond component cost. Diagnosing and repairing wiring issues consumes valuable technician hours, while unexpected downtime interrupts production schedules, affects delivery commitments, and strains customer relationships. In the off-highway sector, unplanned maintenance can translate into thousands of dollars per hour in lost operation.

Traditional field-wired or crimp-style connectors offer flexibility but introduce multiple potential failure points—each splice, backshell, and termination representing another opportunity for moisture ingress or vibration fatigue. Recognizing this vulnerability, Canfield Connector applied decades of expertise in encapsulated and overmolded electronics to reimagine what a sealed connector could be.

The GTMC Duo Connector emerged from that initiative as a compact, dual-circuit solution that merges Deutsch-style reliability with advanced overmolding. Its development marks a shift toward integrated connectivity—moving from repair-prone assemblies to engineered, field-proof solutions designed for the life of the machine.

The Problem: Hidden Costs of Connector Failures

Electrical connectors are among the smallest and least expensive parts of an industrial or mobile system, yet their failure can trigger the most expensive consequences. When a connector loosens, corrodes, or loses continuity, the result is not just an interrupted circuit—it is a halted process, an idle operator, and a repair ticket that ripples through production schedules. The cumulative impact of these events often escapes visibility because connector-related issues are scattered across maintenance logs and service calls rather than grouped as a single root cause.

Downtime and Labor Costs

A technician tracing a signal loss in a harness must often dismantle panels, remove protective covers, or replace entire cable runs to locate a defective junction. Each of these steps consumes labor hours that could otherwise support production. In mobile equipment such as excavators or sprayers, travel and diagnostic time add to the bill. Industry studies estimate that the average cost of unplanned downtime in manufacturing exceeds $10,000 per hour, while a single connector failure in a mobile machine can sideline a six-figure asset for half a day or more.

Environmental Exposure

Standard field-wired connectors are repeatedly challenged by the realities of temperature swings, chemical washdowns, and mechanical vibration. Minute gaps in seals or backshell threads invite moisture ingress; condensation, hydraulic oil, and fertilizer dust combine to create electrolytic corrosion on contacts. Once oxidation begins, resistance increases, signal integrity drops, and intermittent faults appear—often under load or vibration when the system is least accessible.

Vibration and Fatigue

Off-highway and industrial machines generate constant shock and movement. Even properly torqued terminations can loosen microscopically over time. Each vibration cycle flexes conductors and crimps, accelerating metal fatigue. Over thousands of hours of operation, this invisible wear transforms secure connections into unstable ones.

Complex Wiring and Human Error

Traditional designs that require two separate connectors per dual-coil valve or manifold double the opportunities for assembly mistakes. Mis-pinned terminals, mismatched wire gauges, or over-crimped seals introduce weak points from day one. Field service repairs compound the problem when replacement connectors are sourced from mixed suppliers or installed without proper sealing compounds.

Hidden Financial Impact

Beyond repair labor, connector failures inflate warranty claims, disrupt logistics, and undermine customer confidence. OEMs must allocate resources for technical support, replacement parts, and goodwill repairs that erode profit margins. For fleet operators, each unscheduled repair not only costs labor and parts but also forfeits revenue from idle equipment.

Taken together, these factors illustrate a paradox of modern engineering: systems that rely on advanced controls and precise electronics are only as reliable as the small connectors that link them. Addressing that vulnerability requires more than incremental improvements—it demands a holistic redesign of the connection itself.

Engineering the Solution: The GTMC Duo Connector

To solve the chronic weaknesses found in conventional connector assemblies, Canfield Connector's engineering team reexamined every variable that contributes to long-term electrical integrity: mechanical stability, sealing, strain relief, and simplicity of design. The result is the GatorMate GTMC Deutsch Style Duo Connector—a fully overmolded dual-connection solution that merges two Deutsch-style terminations into a single, compact housing engineered for durability and reliability in the harshest operating conditions.

Integration by Design

The GTMC's fundamental innovation lies in consolidation. By combining two independent Deutsch connectors into one overmolded body, the design immediately removes half the junctions and potential leak paths present in conventional dual-connector harnesses. Fewer connectors mean fewer sealing interfaces, reduced assembly time, and a cleaner, more compact footprint. This integrated structure not only simplifies installation but also minimizes human assembly error—a common source of electrical failures in the field.

Advanced Overmolding Process

At the core of the GTMC's performance is Canfield Connector's proprietary overmolding process. During production, pre-terminated leads are precisely positioned within a custom mold cavity, then encapsulated with a specialized thermoplastic elastomer compound. This material permanently bonds to the cable jacket and connector interface, creating a single, unified assembly that is both electrically insulated and mechanically reinforced.

Unlike field-wired connectors that rely on O-rings, backshells, or manual assembly steps, overmolding produces a continuous barrier against moisture, oils, and particulates. The molded strain relief at the cable exit eliminates the sharp bend points where conductors typically fatigue. The resulting geometry distributes mechanical stress evenly, ensuring stable electrical continuity through thousands of vibration and thermal cycles.

Material Engineering for Harsh Environments

The GTMC employs high-performance polymers selected for chemical resistance and thermal stability. The elastomeric overmold maintains flexibility and adhesion from –40°C to +125°C, resisting cracking and delamination even after prolonged UV or fluid exposure. The Deutsch-style inserts retain their proven pin-and-socket design, offering mechanical polarization and positive locking that ensure consistent mating force and contact pressure. Together, these materials deliver IP67 ingress protection, meaning the connector is fully dust-tight and capable of withstanding immersion in one meter of water for 30 minutes without leakage.

Mechanical Precision and Compatibility

Dimensional tolerances are tightly controlled to maintain full backward compatibility with existing Deutsch DT-series connectors. The GTMC mates seamlessly with standard DT receptacles, allowing OEMs to integrate it into existing harnesses without altering interface geometry. This compatibility preserves legacy system flexibility while upgrading environmental protection and mechanical robustness.

Customization and OEM Flexibility

Because the GTMC is manufactured in-house, Canfield Connector can tailor wire lengths, gauges, and jacket materials to match specific application requirements. Options include PVC,

PUR, or TPE jackets for chemical or abrasion resistance, as well as color-coding for simplified assembly. For OEM engineers, this customization capability reduces the need for secondary harness fabrication and streamlines bill-of-material management.

Engineered for Reliability
Every GTMC undergoes 100% electrical continuity testing and visual inspection prior to shipment. Combined with Canfield's ISO 9001–certified manufacturing standards, this ensures each connector leaving production meets exacting performance specifications.

By rethinking the connector as a single integrated component—rather than an assembly of separate parts—Canfield Connector created a solution that addresses both the mechanical and electrical weaknesses inherent to traditional wiring. The GTMC Duo Connector exemplifies how careful design and materials science can transform a simple connection into a strategic advantage for OEMs demanding reliability in every circuit.

Design Advantages for OEMs

For original equipment manufacturers (OEMs), connector reliability is not only an engineering concern but also a direct contributor to profitability. Every assembly step, every warranty claim, and every hour of field service traces back to design choices made long before a machine reaches the customer. The GatorMate GTMC Deutsch Style Duo Connector delivers quantifiable advantages for OEMs seeking to improve reliability, streamline production, and reduce lifetime system costs.

Simplified Assembly and Reduced Labor
Traditional dual-connector harnesses require separate crimping, termination, and sealing steps—each introducing opportunities for error. The GTMC condenses this into a single plug-and-play unit. By integrating two Deutsch-style connections into one overmolded body, the GTMC reduces connector count by 50%, cutting installation time significantly. OEM assembly technicians no longer have to manage multiple connectors or verify redundant seals, which translates to faster builds and fewer quality-control checks.

Lower Warranty and Service Costs
Connector-related failures are among the leading causes of warranty claims in electrically controlled systems. By eliminating potential ingress paths and reducing manual assembly steps, the GTMC virtually removes the most common failure points. The result is fewer field failures, lower warranty costs, and improved customer satisfaction. Each connector represents not just a part savings but an ongoing reduction in total cost of ownership.

Compact, Efficient System Design
The GTMC's dual-circuit integration reduces wiring clutter, creating cleaner valve manifold

layouts and more space-efficient harness routing. The molded body provides consistent geometry for automated or semi-automated assembly, while backward compatibility with Deutsch DT interfaces ensures drop-in adoption with minimal re-engineering.

Custom Configuration and Branding
Canfield Connector's in-house manufacturing allows OEMs to specify wire gauges, lengths, and jacket materials tailored to environmental and electrical demands. Optional color coding, labeling, or custom overmold markings support brand visibility and assembly traceability.

By merging electrical performance, mechanical reliability, and production efficiency, the GTMC Duo Connector enables OEM engineers to design equipment that performs better, lasts longer, and costs less to build and maintain.

Application Examples

The true measure of a connector's value lies not in its specifications but in how it performs in the field. The GatorMate GTMC Deutsch Style Duo Connector was developed with real-world equipment in mind—machines that operate outdoors, encounter vibration daily, and are serviced by technicians who demand reliability without added complexity. Across industries, the GTMC is redefining how OEMs think about connectivity in harsh environments.

Agricultural Machinery
Fertilizer spreaders, seeders, and sprayers operate in conditions that combine moisture, dust, and corrosive chemicals. Field wiring in these systems is routinely exposed to washdowns and flexing harnesses that challenge traditional connectors. The GTMC's overmolded body forms a continuous seal against liquid and debris, while its dual-connection format simplifies valve control wiring for multi-section sprayer manifolds. Less time in assembly means faster machine builds, and fewer connectors in the harness mean fewer opportunities for failure during harvest.

Construction and Off-Highway Equipment
On excavators, loaders, and skid-steers, vibration is constant. Traditional field-wired connectors often loosen or chafe after months of operation, resulting in intermittent electrical faults that are costly to diagnose. The GTMC's integrated strain relief and overmolded encapsulation absorb mechanical shock, maintaining stable contact pressure over thousands of vibration cycles. OEMs benefit from fewer service callbacks and better reliability in the toughest conditions.

Industrial Automation and Pneumatics
In automated systems and fluid-power controls, wiring organization is critical. The GTMC reduces clutter in control panels and on valve manifolds, providing a compact and professional

wiring appearance while improving accessibility for maintenance teams. Its IP67 rating makes it ideal for washdown zones or environments with oil mist and particulates.

Across all these applications, the GTMC doesn't just protect against environmental hazards—it simplifies design, reduces assembly time, and delivers peace of mind to the engineers and technicians who depend on consistent electrical performance day after day.

Conclusion

Electrical systems are only as reliable as their weakest connection. In many cases, that weak link isn't a circuit board or a sensor—it's the connector that joins them. The GatorMate GTMC Deutsch Style Duo Connector was engineered to eliminate this long-standing vulnerability by addressing every failure mode that plagues traditional field-wired assemblies: moisture intrusion, vibration fatigue, and inconsistent sealing.

By integrating two Deutsch-style interfaces into one overmolded body, the GTMC redefines what rugged connectivity can look like. It transforms a pair of potential failure points into a single, unified connection that is simpler to install, easier to maintain, and tougher to break. The result is measurable reliability that translates directly into uptime, productivity, and reduced total cost of ownership.

For OEMs, the GTMC's advantages are both technical and economic. It reduces assembly steps, eliminates redundant materials, and enhances brand reputation through proven field durability. For equipment operators, it provides confidence that every signal will transmit cleanly—no matter the vibration, heat, or exposure the machine endures.

As industrial and mobile systems continue to evolve toward greater automation and higher performance demands, the importance of connector reliability will only grow. The GTMC Duo Connector demonstrates how thoughtful engineering and advanced materials can transform a common failure point into a lasting strength.

Why Canfield Connector

For more than four decades, Canfield Connector has been a trusted innovator in engineered electrical and electronic connection solutions for industrial automation, mobile hydraulics, and fluid power applications. From its headquarters and manufacturing facilities in Youngstown, Ohio, Canfield has built a reputation on precision design, responsive engineering support, and products that perform reliably in the field—not just on paper.

The company's product line extends well beyond standard connectors to include timers, sensors, and custom-engineered interconnect systems for OEMs around the world. Every product is manufactured under ISO 9001–certified processes, with 100% testing and traceability to ensure consistent quality. This commitment to performance and craftsmanship is the foundation behind every connector that carries the Canfield name.

For OEMs seeking a partner rather than just a supplier, Canfield Connector delivers the rare combination of proven reliability, responsive customization, and American-made quality that keeps machines running—and reputations strong.



Canfield Connector's GatorMate GTMC Deutsch Style Duo Connector